

Express Mailing Label No. EF 244382670 US

PATENT APPLICATION

Docket No. SLA 1068

UNITED STATES PATENT APPLICATION

of

SACHIN DESHPANDE

and

RENJIT TOM THOMAS

for

**METHODS AND SYSTEMS FOR
SCALABLE STREAMING OF IMAGES WITH CLIENT-SIDE
CONTROL**

Related References

This application is filed as a continuation-in-part of United States Patent Application Serial No. 09/709,985, titled "Methods and Systems for Transmitting Digital Images," filed November 10, 2000 by Deshpande et al.

The Field of the Invention

Embodiments of the present invention relate to methods and systems for managing and transmitting image data. Some embodiments are particularly suited to streaming JPEG 2000 images from a web server.

Background

In many Internet and network applications, large image files are frequently transferred. These large image files must be transmitted from server to client with accuracy and speed. When connection speeds are not optimal, these images can take an inconveniently long time to download to a client. Using known methods, this extended lag results in high latency or delay before display of the complete image.

Image files can also be problematic when their size, resolution or other attributes are not optimized to the needs of the user.

JPEG 2000 is an image compression standard with the ability to support large images. JPEG 2000 also supports resolution, quality and region-of-interest scalability. Thus, the JPEG 2000 bitstream is scalable. However the server-client protocol to get only part of the JPEG 2000 bitstream is not defined. Details of the JPEG 2000 standard may be accessed by reference to JPEG 2000 Part 1 Final Committee Draft Version 1.0, ISO/IEC JTC 1/SC 29/WG 1 N1646, March 2000 and JPEG 2000 Verification Model 7.0 (Technical

the length of each packet 10, 12 can be obtained from the main header 2 or derived from the packet headers located in the main header 2 or in the codestream 14. Based on this information and the length of code-block contribution information included in each packet header, we can identify the locations/segments of the codestream for a particular code-block, precinct, resolution, component and layer. In fact, an index file can be generated to record this indexing information by parsing the codestream headers, including the main header 2, tile-part headers 4 and packet headers 14. This index file can then be used to facilitate the retrieval of a particular portion of the codestream.

For a given tile, the order in which the packets are interleaved is called the progression order. The interleaving of the packets can progress along four axes: layer, component, resolution and precinct. There are five allowable progression orders in the standard which are signaled by the COD and/or Progressive order change default (POD) markers in the main header 2.

1. Layer-resolution-component-position progressive,
2. Resolution-layer-component-position progressive,
3. Resolution-position-component-layer progressive,
4. Position-component-resolution-layer progressive,
5. Component-position-resolution-layer progressive.

SUMMARY OF THE INVENTION

Embodiments of the present invention comprise methods and systems that allow customized transmission of image files over a network. Embodiments of the present

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the manner in which the above-recited and other advantages and objects of the invention are obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 is a diagram showing elements of an exemplary image file structure;

Figure 2 is a diagram of a computer screen displaying a thumbnail interface of some embodiments of the present invention;

Figure 3 is a diagram of a computer screen displaying a resolution scalability function on a thumbnail interface of some embodiments of the present invention; and

Figure 4 is a diagram of a computer screen displaying a full resolution image on a thumbnail interface of some embodiments of the present invention.

DETAILED DESCRIPTION

The currently preferred embodiments of the present invention will be best understood by reference to the drawings, wherein like parts are designated by like numerals throughout. The figures listed above are expressly incorporated as part of this detailed description.

It will be readily understood that the components of the present invention, as generally described and illustrated in the figures herein, could be arranged and designed in a wide variety of different configurations. Thus, the following more detailed description of the embodiments of the methods and systems of the present invention is not intended to limit the scope of the invention but it is merely representative of the presently preferred embodiments of the invention.

Elements of embodiments of the present invention may be embodied in hardware, firmware and/or software. While exemplary embodiments revealed herein may only describe one of these forms, it is to be understood that one skilled in the art would be able to effectuate these elements in any of these forms while resting within the scope of the present invention.

Some embodiments of the present invention are explained in reference to a specific embodiment which employs an HTTP protocol for streaming images in the JPEG2000 format. While this is used as a primary example, other protocols and image formats may be used in embodiments of the present invention.

In some embodiments, the above described features and/or other features may be implemented using a client application which downloads the target image at a reduced resolution and displays that image as a “thumbnail” for user manipulation, reference and

input such as ROI selection and other selection. Once the thumbnail has been downloaded and displayed, a user may select a portion of the image for display at a resolution higher than that of the thumbnail. A user may select a ROI on the thumbnail or on a higher-resolution image using many known input device methods. Generally, a rectangular region will be delineated by a series of inputs, such as mouse clicks, and the client application will request the portion of the image corresponding to the designated region of interest. In this manner, a portion of the image may be displayed without waiting for display of the entire image.

Some embodiments of a client application may provide for selection of image resolution. Typically, for large, high-resolution images, there will be a range of resolutions between the maximum image resolution and a minimum thumbnail resolution. These embodiments will allow a user to select an optimum resolution below the maximum image resolution which will reduce latency.

A client application of embodiments of the present invention may also allow a user to select whether quality scalability is enabled. When enabled, quality scalability can render relevant image details prior to complete image transmission thereby allowing a user to make image decisions prior to complete transmission of the image. Quality scalability may be applied to the thumbnail used for ROI selection as well as the target image.

In a parent application, the inventor introduced an index file concept which allows a client to make intelligent HTTP requests to obtain required portions of an image file bitstream, such as a JPEG 2000 bitstream, from a web server. Embodiments of the present invention may utilize index file methods while other embodiments may operate without index files. Embodiments of the present invention comprise image data streaming methods and systems which employ client side parsing to customize and modify the image data. The

architectures of these embodiments may be web based and may use HTTP protocols. These methods can be used without any explicit index file.

Known methods include a set of application programming interfaces (APIs) for random access of segments of JPEG2000 file and an architecture for cache management, network packetization and packet loss recovery for JPEG2000 files. There are several drawbacks of this approach. It needs a proprietary server to support the above features, whereas embodiments of the present invention may work with any standard HTTP 1.1 web server or other servers configurations. Some embodiments may be used with any HTTP 1.1 server supporting byte-ranges. Several commercial and free HTTP servers exist which are compatible with embodiments of the present invention.

HTTP runs on top of TCP/IP, which supports reliable packet delivery. Caching is also supported by HTTP. Unlike audio and video data, which have real-time properties and thus cannot be optimally transmitted using TCP/IP, the JPEG2000 images can be transmitted using this reliable delivery mechanism. Whereas error concealment and error resilience are active research areas for video and audio data, an image (i.e., JPEG2000) typically needs to be transported reliably and any packet loss is better handled by re-transmission. Accordingly, embodiments of the present invention utilize web server based streaming for JPEG 2000 images. This allows easy deployment since standard web servers can host the JPEG2000 images.

Client-Side-Parsing-Based Streaming

Embodiments of the present invention comprise methods and systems which utilize client-side-parsing-based (CSPB) streaming in which a server may host an image

for the architecture for thumbnail generation is shown below:

```
open connection to the server;
while (parsing of main headers not complete)
{
    read n bytes of data from the server;
    parse and decode the read bytes ;
}

while (bytes required for reconstructing thumbnail
resolution not complete)
{
    read n bytes;
    parse and decode the read bytes;
}

}
close the connection;
```

Transmission of Higher Resolution Images

Once the thumbnail data for an image has been acquired, it may be displayed to the user as an aid for user input or as some other form of reference. Using many methods, a user may request a higher resolution version of the image. A connection to a server is established and small chunks of data are read. These data chunks are then parsed until sufficient data is obtained to decode up to the selected resolution. The pseudo code to obtain any particular user specified resolution of the image from the server is described below for some embodiments:

```
If the local system has cached the already read bytes
{
    Retrieve the already read bytes from the local system
    cache;
    Decode the bytes till the previous achieved resolution;
    Open connection to remote server;
}
else
{
```

```

    Open connection to remote server;
    while (parsing of main headers not complete)
    {
        read n bytes of data from the server;
        parse and decode the read bytes ;
    }
}

while (desired resolution not achieved)
{
    while ( bytes required for reconstructing current
resolution not complete)
    {
        read n bytes;
        parse and decode the read bytes;
    }
    reconstruct the current resolution;
    increase the resolution count;
}
close the connection;

```

Quality scalability and region-of-interest (ROI) scalability can be achieved similarly by obtaining the required portions of an image file such as a JPEG2000 bitstream.

Streaming Selected Portions of the Codestream

Since a JPEG2000 codestream is well structured, it is possible to retrieve some portion of the codestream for a particular interest. Some typical applications are resolution scalability, quality scalability and region of interest streaming. The locations of the corresponding portions of the codestream for these applications are described below.

Resolution Scalability. If the progression order follows Order 2 or Order 3 as described in the background section above, then the data for a particular resolution will be a contiguous segment in the codestream. If the progression order follows Order 1, then the data for a particular resolution will be distributed over several separate contiguous segments (one in each quality layer) in the codestream. If the progression order follows

Order 4 or 5, then the data for a particular resolution will again consists of several separate contiguous segments in the codestream, with one segment in each precinct and each component.

SNR (quality) Scalability. It is also relatively easy to achieve SNR scalability, especially when the codestream follows the first progression order. For the other progression orders, the data for a particular quality layer is distributed over several separate contiguous segments in the codestream. Their locations can be obtained from the index file or by doing on-the-fly parsing of the bitstream.

Region of Interest (ROI) Streaming. Region of interest streaming is more computationally involved as compared to the above two cases. For an arbitrary region in the spatial domain, we need to trace how each coefficient and pixel value is reconstructed in the inverse wavelet transform, and find the corresponding region in each sub-band that contributes to the reconstruction of the ROI. The precincts and code-blocks that are needed to reconstruct the ROI can then be identified. The compressed data for these precincts and code-blocks can then be located and retrieved at the server side for streaming.

Some embodiments of the present invention implement client-side-parsing-based streaming for JPEG 2000 images as a Java applet. An example of these embodiments is shown in Figure 2 where the initial appearance of a web page 20 with thumbnails 22 is shown. Thumbnails 22 may be automatically generated by the client-side-parsing-based streaming as described above. Buttons, drop-down menus, dialog boxes and other user interface controls 24 may be used to obtain user data. User interface controls 24 may be used to obtain user preferences regarding image resolution, quality scalability and other data. Thumbnails 22 may be used to select a particular image or portion thereof. A

region-of-interest (ROI) may be selected by clicking and dragging a particular area on one of the thumbnail images. Once user preferences are identified, the image may be streamed to the client in the preferred format. As shown in Figure 3, an image 30 may be streamed at a prescribed resolution that is lower than the maximum resolution available for the image. This can save transmission time and resources. The user may also select to view the image at the highest available resolution 40 as shown in Figure 4.

Intermediate steps in the decoding typically utilize large amounts of resources (e.g. memory); however these are released once the decoding is over. The current web browsers also typically may put restrictions on the number of simultaneously open connections to the server. To take care of these issues, some embodiments take advantage of the fact that the different instances of the same applet class are running in the web browser. The execution of the applets is then serialized by locking and releasing the shared resources.

Some embodiments use HTTP/1.1 protocol to stream JPEG2000 images from a web server. Other embodiments may also use other similar protocols and similar image formats.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

I claim: